


# PRODUCT GREEN GUIDE

## Trifab™ 400 Framing System

Trifab™ 400 Framing System is a proven solution for storefront and low-rise applications.



## RATING SYSTEMS

### LEED v4 BD+C: New Construction

- EA: Optimize Energy Performance
- EA: Renewable Energy Production
- MR: Environmental Product Declarations
- MR: Sourcing of Raw Materials
- MR: Material Ingredients
- MR: Source Reduction - Lead, Cadmium, and Copper
- MR: Construction and Demolition Waste Management
- EQ: Thermal Comfort
- EQ: Daylight
- EQ: Quality Views
- EQ: Acoustic Performance

### Living Building Challenge 3.1

- |  |  |
|--|--|
| <input type="radio"/> IMP 06: Net Positive Energy              | <input type="radio"/> IMP 12: Responsible Industry               |
| <input type="radio"/> IMP 07: Civilized Environment            | <input checked="" type="radio"/> IMP 13: Living Economy Sourcing |
| <input checked="" type="radio"/> IMP 08: Healthy Interior      | <input checked="" type="radio"/> IMP 14: Net Positive Waste      |
| <input checked="" type="radio"/> IMP 09: Biophilic Environment | <input type="radio"/> IMP 16: Universal Access                   |
| <input checked="" type="radio"/> IMP 10: Red List              |  |

### WELL Building Standard

- |  |  |
|--|--|
| <input checked="" type="radio"/> 01: Air Quality Standards       | <input checked="" type="radio"/> 28: Cleanable Environment       |
| <input type="radio"/> 03: Ventilation Effectiveness              | <input checked="" type="radio"/> 54: Circadian Lighting          |
| <input checked="" type="radio"/> 04: VOC Reduction               | <input type="radio"/> 56: Solar Glare Control                    |
| <input type="radio"/> 08: Healthy Entrance                       | <input checked="" type="radio"/> 61: Right to Light              |
| <input checked="" type="radio"/> 11: Fundamental Material Safety | <input checked="" type="radio"/> 62: Daylight Modeling           |
| <input checked="" type="radio"/> 12: Moisture Mgmt               | <input checked="" type="radio"/> 63: Daylight Fenestration       |
| <input checked="" type="radio"/> 14: Air Filtration Mgmt         | <input type="radio"/> 72: Accessible Design                      |
| <input type="radio"/> 15: Increased Ventilation                  | <input checked="" type="radio"/> 74: Exterior Noise Intrusion    |
| <input type="radio"/> 19: Operable Windows                       | <input type="radio"/> 76: Thermal Comfort                        |
| <input checked="" type="radio"/> 25: Toxic Material Reduction    | <input checked="" type="radio"/> 97: Material Transparency       |
| <input type="radio"/> 26: Enhanced Material Safety               | <input checked="" type="radio"/> 98: Organizational Transparency |

## FEATURES

- 1-3/4" (44.5mm) sightline
- 4" (101.6mm) depth
- Non thermal performance
- Center glazed
- Flush glazed from either the inside or outside
- Screw Spline, Shear Block or Stick fabrication
- Single-span
- Standard anodized finishes only

## DOCUMENTS



### Environmental Product Declaration

Document no. 47868332121.104.1  
Product-specific Type III EPD



### Material Transparency Summary

Document no. MTSC020EN  
Manufacturer Material Ingredient Inventory